

ReliChrom™ SP400/SS

Lot. E905C126

Column dimensions:

Internal Diameter i.d.0.8 cmLenght10 cmArea0.5 cm²Resin volume5 ml

Theoretical plates N 1640 m⁻¹
Asymmetry A_s 0.95

Experimental conditions

Sample 100 µl 1% Acetone (v/v)

Mobile phase 50 mM TRIS/HCl, 0.9% NaCl, pH 8.0

Flow velocity 1.25 ml/min

Instructions for use

Preliminary set up:

- Rinse the chromatographic system circuit with DI water;
- After the removal of the upper stopper of the ReliChrom™ column, connect it to the chromatographic unit;
- Remove the bottom stopper of ReliChrom™ column and connect the column outlet to the specific device of your chromatographic system (Detectors, fraction collector...).


Operation mode:

- wash out the conditioning solution with 10 BV of DI water;
- start the equilibration with the desired buffer solution at an appropriate linear flow rate;
- run the chromatographic separation according to your individual protocol at the same flow rate as in the previous step;
- if necessary, perform a regeneration step following the instructions here below:
 - Condition the resin with 1 BV of NaOH 0.5 M
 - Displace the base with 2 BV of DI water
 - Regenerate with 1 1.5 BV HCl 0.5 M
 - Displace the acid with 2 BV of DI water
 - Condition the resin with 2 BV NaCl 0.5 1M
 - Rinse with 5 10 BV of DI water

Lysozyme capacity vs linear velocity

Feed solution: 8 g/l Lysozyme in 20 mM sodium acetate buffer, pH 5

Buffer equilibration: 6 BV sodium acetate buffer 20 mM, pH 5 **Displacement:** 6 BV sodium acetate buffer 20 mM, pH 5 **Elution:** 6 BV sodium acetate buffer 20 mM, pH 5 + NaCl 1M



Notice:

All data and suggestions made herein are based upon our research and are believed to be accurate. However, no guarantee is made or implied since conditions and methods of use of our products are beyond our control. Our products are sold on the conditions that the user will evaluate them himself, as well as our formulae and recommendations, to determine their suitability for his own purpose. Also, statements as to the use of our products are not be construed as recommendations for their use in the infringements of any patent.

Via Roma, 55 – 20082 Binasco (MI) Italy **Phone**: 0039.02.900130221 – 223 **Fax**: 0039.02.90090774

 $\textbf{e-mail}: \underline{info@resindion.com} - www.resindion.com$